



FEATURES

- Steel shell
- Air or water condensation
- Sanitization cycle
- Programmable ice production
- Capacitive control key
- Audible and light signaling alarms
- HACCP Alarm Report
- External cube weight adjustment
- USB connection for sw update and HACCP data download
- Condenser fan controlled at low ambient temperatures
- Programmable ice production
- Predictive failure analysis
- Equipment performance report

OPTIONAL

- Programmable sanitizing cycle with ozone
- Nanotechnological evaporator treatment with Rainbow Technology



RECOMMENDED DEPOSITS

42,0 kg
2100 pcs

DIMENSIONS

L x P x H (mm)



700 x 580 x 995



760 x 640 x 1080

VOLTAGE



220-240/50/1
220/60/1

GAS



R290
GWP 3

TECHNICAL DATA

											
			cond	comp. W	ABS. W	Fuse	Kwh/100Kg	I / h	Kg	Kg	
JS70	A AG	220-240/50/1N		1315	620	10	20.9	10.3	53	62	
JS70	W AG	220-240/50/1N		1315	490	10	18.3	45.8	53	62	

ICE TYPE

	PCS / CYCLE PZ / CICLO	WEIGHT ICE PESO GHIACCIO
	Full Ice Cube 20 g -70/90 35 x 37 x 32 mm	56 20 g

ICE PRODUCTION

kg/24h
lbs/24h

Air cooling





Temp. Aria Air Temp.	Temp. Acqua /Water Temp.			
°C / °F	10° 50°	15° 59°	21° 70°	32° 90°
10° 50°	70 154	69 152	67 148	63 139
21° 70°	65 143	63 139	61 134	57 126
32° 90°	60 132	58 128	56 123	52 115
38° 100°	49 108	47 104	45 99	42 93

Water cooling



Temp. Aria Air Temp.	Temp. Acqua /Water Temp.			
°C / °F	10° 50°	15° 59°	21° 70°	32° 90°
10° 50°	75 165	73 161	71 156	64 141
21° 70°	72 159	70 154	68 150	61 134
32° 90°	70 154	68 150	64 141	59 130
38° 100°	63 139	62 137	59 130	54 119

DIMENSIONS





- B** Electrical cable supply
Ingresso alimentazione
elettrica
- C** Water outlet connection
Attacco scarico acqua
Ø 20 mm
- D** Water outlet connection
water condensation / Uscita
acqua condensatore ad
acqua Ø 20 mm- 3/4"G
- E** Water inlet connection / Attacco
entrata acqua - 3/4"G



ICEWORLD

Allows control and monitoring of ice makers directly from smartphones / Allows control and monitoring of ice makers directly from smartphones



Operating conditions

	Min	Max
Temp. Ambient	10°C	40°C
Temp. Water Ice	5°	35°
Water Pressure	1 Bar (14psi)	10 Bar (140psi)
Conductivity water	20 microS	500 microS
Power Supply	-10%	+10%

TOUCH CONTROL



Capacitive Stand-by / Start button
(LED continuously changing colors from white to red)

Heat expelled	1938 W
Air Volume	310 m³/h